

DEFOAMER-C

Recovery Tank Defoamer



FEATURES

- Concentrated
- Polysiloxane emulsion
- Defoams soaps, detergents, foaming soils

BENEFITS

- Efficient to use
- · Highly effective foam suppressant
- · Prevents all foaming problems

RECOMMENDED USES

Elimination of foam in the carpet extraction recovery tank.

SPECIFICATIONS

Color:Milky whitepH use dilution:7.25 - 8.5Scent/Odor:None addedPhosphorus content:0.0%Character:Opaque, viscous liquidApprovals:cRc

Foam: Non-foamer



IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Appropriate sprayer or measuring device.

DIRECTIONS TO USE

Shake well before using. Use as is – do not dilute. Spray the concentrate on to extractor recovery tank walls using a hand sprayer or pour 1-2 ounces into end of extractor vacuum hose with machine running. For excessive foaming, increase amount of product used. If foaming occurs during cleaning, spray the concentrate directly on to foam in recovery tank as needed.

NOTE: Avoid spraying on hard or resilient floors as it may cause slipperiness.

PACKAGING

This product is available in 4/1 gallon cases (5013071).

Copyright© 2015 U S Chemical, Watertown WI 53094 www.uschemical.com 04/15

L003603