

GT-2000

The Ultimate Floor Finish



FEATURES

- Ultra high gloss
- Durable, scuff resistant formula
- For all buffing speeds

BENEFITS

- Superior floor appearance
- Long lasting good looks
- Works in multiple applications

RECOMMENDED USES

For most types of resilient floors - vinyl, linoleum and rubber.

SPECIFICATIONS

Color : White **Scent/Odor:** Bland

Character: Opaque, non-viscous liquid

Foam : Non-foamer

pH use dilution : 7.6-8.6 Phosphorus content : 1.5% Approvals : N/A



IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Clean mop on final application, pail, buffing machine and pads.

DIRECTIONS TO USE

Blockade areas to be stripped or finished.

PREPARATION: If a complete start over is desired, remove old finish using a Misco stripper of your choice. If a partial or controlled removal of finish is desired, follow the directions on Misco Sustain. Rinse floor completely with clean water and allow to dry. It is advisable to strip floors that are coated with soft finishes.

SEAL: Misco recommends a sealer coat of Begin on resilient floors (except pure vinyl tiles or sheeting).

APPLICATION: Apply GT 2000 using a clean mop (pre-rinse in clean water and wring out before using). On floors where all finish has been removed, apply two coats of GT 2000. Three coats may be desirable, where extreme traffic conditions are present or where propane buffers are used. Allow 45 minutes drying time between coats.

MAINTENANCE: For routine damp mop, wet-mop or machine scrubbing procedures, use Misco Sustain as recommended. Additional coats of GT 2000 may be applied as required to maintain the desired standard of gloss and protection.

NOTE: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials.

PACKAGING

This product is available in 4/1 gallon cases (5107819) and 5 gallon pails (065637).

L003669

Copyright© 2015 U S Chemical, Watertown WI 53094 www.uschemical.com 03/15