




# SUCCESS

*Metallic Floor Finish*



## FEATURES

- Self polishing
- High gloss
- Spray buffable
- Excellent durability

## BENEFITS

- Reduces buffing / labor time
- Floors look great
- Easy to maintain
- Reduces stripping frequency

## RECOMMENDED USES

For most types of resilient floors - vinyl, linoleum and rubber.

## SPECIFICATIONS

**Color** : White

**Scent/Odor**: Bland

**Character** : Opaque, non-viscous liquid

**Foam** : Non-foamer

**pH use dilution** : 7.8-8.8

**Phosphorus content** : 1.0%

**Approvals** : N/A

**Solids** : 19%



## IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

## PRODUCT DIRECTIONS

### EQUIPMENT TO USE

Clean mop on final application, pail, buffing machine and pads.

### DIRECTIONS TO USE

**PREPARATION:** Blockade areas to be stripped or finished. Floors will be very slippery until dry. Remove old finish using Take-Off. If partial or controlled removal is desired, use Sustain. Rinse floor completely with clean water and allow to dry prior to application of Success. **APPLICATION:** Apply Success using a clean mop. It is recommended that the mop first be rinsed in clear water and completely wrung out before using. On floors from which all finish has been removed, apply a minimum of two coats of Success; three coats for older, more porous floors. On highly porous floors, including some terrazzos, application of a sealer such as Begin may be necessary. Follow with two coats of Success. Allow 20-30 minutes drying time between coats. **MAINTENANCE:** Remove loose surface soil using a dry mop treated with Misco Dust Mop Treatment. Damp mop with Sustain to remove lightly embedded surface soil. For heavier soil build-up, scrub the floor using Sustain and a floor machine. For occasional spray-buffing use 1:1 solution of water and Success. Additional coats may be applied later to build up more protection and gloss. It is recommended that no more than three coats be applied at ONE time. One gallon of Success will cover approximately 4000 square feet per coat. For Best Results: To avoid contamination do not return unused portions to the original container. Do not use on surfaces colder than 50 °F/10 °C. Note: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.

## PACKAGING

This product is available in 4/1 gallon cases (5107763) and 5 gallon pails (65633).

L003672

Copyright© 2015 U S Chemical, Watertown WI 53094  
www.uschemical.com

03/15