



FEATURES

- Excellent cleaning
- Multi-purpose product
- Reduces the risk of slip and fall accidents

BENEFITS

- Great for everyday use
- Use full strength for traction treatment
- Helps create a safer work environment

RECOMMENDED USES

Heavy duty floor cleaning and traction treatment for quarry tile. Also excellent for cleaning porcelain and glazed ceramic tile.

SPECIFICATIONS

Color : Orange

Scent/Odor: None added

Character : Clear, non-viscous liquid

Foam : Moderate to low

pH use dilution : 4.25-5.25

Phosphorus content : 0.00%

Approvals : cRc



IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

MixMATE Sanitation System, appropriate MixMATE spray bottle or pail and mop, sponge, cleaning cloth, bowl mop, scrub brush, rubber gloves and eye protection.

DIRECTIONS TO USE

For use in industrial, institutional and/or food processing establishments. Do not store product in food processing areas. Prior to use, all food products and packaging material shall be removed or protected to avoid contamination of food and food contact surfaces. A potable water rinse is required after use on all surfaces. Floor Cleaning - 1) Wipe up spills and sweep debris from floor surface. 2) Dispense at a ratio of 1 ounce per gallon of cold or hot water (8 mL per liter). 3) Apply solution to floor surface using a dripping wet mop. 4) Aggressively scrub the floor with a deck brush. 5) Mop up soiled solution or squeegee to drain. 6) Rinse or damp mop floor surface clean. 7) Dry floor surface using a dry mop or squeegee. Traction Treatment - Once a month or spot treat slippery areas as needed. 1) Wipe up spills and sweep debris from floor surface. 2) Apply full strength (straight from bottle) in area to be treated. 3) Evenly spread across the surface using deck brush. Allow to remain on floor surface: 20 minutes for quarry tile / 40 minutes for glazed & porcelain tile. (DO NOT ALLOW to dry on surface during standing time.) 4) Mop up soiled solution or squeegee to drain. 5) Rinse or damp mop floor surface clean. 6) Dry floor surface using a dry mop or squeegee. Concrete Cleaning - 1) Sweep all debris from area to be cleaned. 2) Dispense at a ratio of 1 ounce per 4 ounces of cold or hot water (250 mL per liter). 3) Apply solution and allow it to stand on area to be cleaned for 3-5 minutes. 4) Aggressively scrub area with a deck brush. 5) Rinse surface clean with tap water. DILUTION RATIO: Daily Floor Cleaning - 1:128, Traction Treatment - Full Strength Concrete Cleaning - 1:4

PACKAGING

This product is available in 2/1 gallons (076953) and 2/3100 mL canisters (4379003).