

LO ODOR STRIPPER

Non-Ammoniated Floor Finish Stripper



FEATURES

- Contains no ammonia
- Concentrated formula
- Works quickly and completely

BENEFITS

- Non-irritating to residents
- Economical in use
- Labor saving

RECOMMENDED USES

Removal of metal cross-linked floor finishes without ammonia odor.

SPECIFICATIONS

Color : Light orange
Scent : None added
Character : Clear, non-viscous liquid
Foam : Low

pH use dilution : 12.0 - 13.0
Phosphorus content : 0.0%
Approvals : cRc

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Clean mop and bucket, scrubbing machine with stripping pads, wet vacuum, personal protective equipment.

DIRECTIONS TO USE

1. **DILUTION:** To remove metal complex finishes and most other polymer finishes - Prepare a 1:12 dilution of LO ODOR STRIPPER with hot water (1 1/2 cups/gallon). For heavy build up and difficult-to-remove sealers, it may be diluted up to 1:4 with hot water (4 cups/gallon). 2. **APPLICATION & SCRUBBING:** Apply the hot solution of LO ODOR STRIPPER to the area to be stripped using a wet mop or from the solution feed tank of a floor machine. Apply the solution liberally to an area no larger than about 10 by 12 feet. Allow 3 to 5 minutes for the solution of LO ODOR STRIPPER to work before scrubbing. In most cases a GREEN or BROWN stripping pad is recommended. For hard surfaces with heavy build ups such as terrazzo and concrete a BLACK pad may be used. 3. **PICK-UP & RINSING:** The used stripping solution should be picked up using a wet vacuum or a mop and bucket. When using a wet vacuum, it is recommended that the floor be rinsed immediately to prevent small amounts of residue from drying on the floor. When using a mop and bucket, the floor should first be soaked with an unwrung mop. This will float the spent solution, along with the old finish, off the floor. Pick up this solution with a wrung-out mop. Rinse the floor completely with clear water. After rinsing you should be able to run your finger across the dry floor without picking up any powdery residue. 4. **DETAILING & EDGING:** To remove finish along base boards, in corners, and around door stops, etc. LO ODOR STRIPPER may be diluted as strong as 1:2 with water. Protective gloves are recommended when solution comes in contact with hands. NOTE: Do not use on wood or cork floors. Some grades of linoleum may be discolored by LO ODOR STRIPPER. Always pre-test the floor with a small amount of solution before stripping.

PACKAGING

This product is available in 4/1 gallon cases (5015210) and 5 gallon pails (064143).