

ENCLOSE PLUS Acrylic Floor Sealer

FEATURES

- Seal and finish in one product
- Maintain with 175-1500 RPM
- Excellent gloss

BENEFITS

- Simplifies hard floor maintenance
- Easy to use and maintain
- Brilliant results

RECOMMENDED USES

Sealing and finishing terrazo, quarry tile, brick, slate, marble and unglazed ceramic and Mexican tile. Can also be used on resilient floors.

SPECIFICATIONS

Color : White
Scent/Odor : None added
Character : Milky, non-viscous liquid
Foam : Non-foamer

pH use dilution : 8.8 - 9.3
Phosphorus content : 0.08%
Non-volatile solids : 20%



IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Appropriate stripping supplies and equipment, dust mop, clean mop, mop bucket, burnishing equipment, deep scrubbing equipment.

DIRECTIONS TO USE

1. Strip floor according to stripper label directions.
2. Apply 2 to 3 coats of ENCLOSE PLUS using a clean mop. If higher gloss is desired apply additional coats.
3. Allow 40-50 minutes drying time between coats.

MAINTENANCE:

1. Dust mop or sweep.
2. Clean floor with a recommended cleaner according to label directions.
3. If desired, spraybuff or high speed buff with a recommended floor maintainer in order to maintain desired gloss.

RECOATING:

1. Dust mop or sweep.
2. Deep scrub floor with a recommended cleaner according to label directions.
3. Apply 1 or 2 coats using a clean mop.

REMOVAL:

1. Remove using other a recommended stripper according to label directions.

PACKAGING

This product is available in 5 gallon BIB (076882).