



GX-2002

Low Maintenance Buffable Floor Finish

FEATURES

- Low maintenance & high durability
- Industry proven formula
- Excellent traffic and mark resistance

BENEFITS

- Great finish value
- Saves time and money
- Protects and enhances floor appearance

RECOMMENDED USES

Low maintenance, high durability floor finishing. For use on all resilient floors.



SPECIFICATIONS

Color : White
Scent : Ammonical
Character : Opaque, non-viscous liquid

pH use dilution : 9.0-9.4
Phosphorus content : 0.08%
Solids : 16.7%

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Mop or floor machine, wet vacuum or bucket with wringer, rubber gloves, eye protection and wet floor signs.

DIRECTIONS TO USE

1. Strip floor using a recommended floor stripper according to label directions.
2. Apply 2-3 uniform coats using a clean mop. If higher gloss is desired apply additional coats.
3. Allow 40-50 minutes drying time between coats.

MAINTENANCE:

1. Dust mop or sweep.
2. Clean floor using a neutral cleaner according to label directions.
3. If desired, spraybuff or high speed spraybuff using GENESIS GX-1000 or GX-1500 to enhance gloss.

BEFORE RECOATING:

1. Dust mop or sweep.
2. Deep scrub floor using a neutral cleaner according to label directions.
3. Apply 1-2 coats using a clean mop.

REMOVAL:

1. Remove using a recommended floor stripper according to label directions.

PACKAGING

This product is available in 4/1 gallon cases (076911) and 5 gallon BIB (076908).