

FLOORIFIC® 2200 PLUS

High Solids Floor Finish

FEATURES

- Does not require daily burnishing
- Applies clear & will not darken
- Responds instantly to burnishing

BENEFITS

- Low UHS maintenance cost
- Enhances light-colored flooring
- Keeps the “wet look”

RECOMMENDED USES

High durability UHS floor finish for resilient flooring.

SPECIFICATIONS

Color : White
Scent : Ammonia
Character : Opaque, non-viscous liquid

pH use dilution : 8.3-9.3
Phosphorus content : 0.1%
Solids : 18.0%



IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Appropriate stripping chemicals and equipment, dust mop, clean mop, mop bucket, deep scrubbing equipment.

DIRECTIONS TO USE

1. Remove all old finish using a recommended stripper according to label directions. If floor is new, be sure to remove the “factory” finish. 2. Apply FLOORIFIC 2200 PLUS in uniform medium coats. Apply additional coats until desired gloss is obtained. Buffing immediately after application is not necessary. 3. Allow 45 minutes drying time between coats. **NOTE:** For improved, long-lasting protection of floor, you may wish to use a base coat as part of your maintenance system. This will allow selective stripping of finish top coat without removal of the protective base coat. Refer to label for complete directions. **MAINTENANCE:** 1. Dust mop or sweep as necessary. The more often you do this, the longer any finish will last. 2. Damp mop or automatic scrub daily using a neutral cleaner according to label directions. 3. After cleaning, burnish floor as needed to maintain “wet look” gloss using propane, battery, or electric ultra high speed buffing equipment. Buff only with ultra high speed buffing pads. 4. At least once per week, deep scrub floor using a blue or green pad and mop apply FLOORIFIC 2200 PLUS diluted 1:4 with cool water to maintain/enhance floor appearance. Allow FLOORIFIC 2200 PLUS to thoroughly dry. Burnish floor after drying to maximize appearance. Frequency of burnishing and use of FLOORIFIC 2200 PLUS will depend on floor traffic conditions.

REMOVAL: 1. When stripping becomes necessary, use a recommended stripper according to label directions.

PACKAGING

This product is available in 4/1 gallon cases (064147) and 5 gallon bag-in-box (064148).