

### Bio-Active Drain Maintainer

#### FEATURES

- Contains no harmful acids, caustics or solvents
- Special bacterial cultures

#### BENEFITS

- Employee safety
- Safe on sinks and drains
- Safely digests organic waste

#### RECOMMENDED USES

For cleaning of grease traps, and the treatment of drains and septic tanks.

#### SPECIFICATIONS

**Color** : White

**Scent/Odor** : Floral

**Character** : Opaque, non-viscous liquid

**Foam** : Low

**pH use dilution** : 6.0 - 8.0

**Phosphorus content** : 0.0%

**Approvals** : cRC



#### IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

#### PRODUCT DIRECTIONS

##### EQUIPMENT TO USE

Manually pour or automatic dispensing system.

##### DIRECTIONS TO USE

Keep from freezing.

**FOR GREASE TRAPS:** For average size grease traps (about 30 cubic feet), use one quart added directly to trap or through drain. Then use one pint per week for maintenance.

**FOR FREE-FLOWING PLUMBING:** Treat drains at least once per week with the recommended amount. Apply at the end of the day or when flow is at the lowest, and treat lower floors first.

Kitchen sinks: 4 ounces

Bathroom sinks: 4 ounces

Mop, laundry sinks: 8 ounces

Floor drains: 4 ounces

Dishwashers: 8 ounces

Urinals, toilets: 2 ounces

Garbage disposal: 8 ounces

Bar sinks, tap drains: 2 ounces

**SEPTIC TANKS:** Use 2 to 4 quarts for initial treatment of 500 gallon tank. For weekly maintenance, use 1 pint for each 5 people on the system. Treat drain fields and leach beds by pouring into the distribution boxes or vents.

#### PACKAGING

This product is available in 4/1 gallon cases (063031) and 5 gallon pails (063032).