



QUICKLINE™ TKO™



FEATURES

- Institutional strength
- Ready to use formula
- Non abrasive formulation

BENEFITS

- Low use cost
- No product mixing
- Does not scratch surfaces

RECOMMENDED USES

For use on grills, ovens, hoods and other stainless steel surfaces.

SPECIFICATIONS

Color : Colorless

Scent : None

Character : Clear, slightly viscous liquid

Foam : Moderate

pH use dilution : >13.0

Phosphorus content : 0.0%

Approvals : N/A

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Clean cloth, rubber gloves and eye protection.

DIRECTIONS TO USE

Rubber gloves and eye protection are recommended. NOTE: For gas ovens, do not spray on pilot light. For electric ovens, do not spray on heating element. Use in either warm (150°–200°F) or cold empty oven. Clean racks separately. Spray foam over interior surface. Allow foam to work 10-15 minutes. Wipe clean with wet cloth, sponge or paper towels. Be sure all foam is removed. Rinse. Repeat if necessary. Do not use on aluminum.

PACKAGING

This product is available in 6/32 oz. cases (5512363).

