

# Touchless Presoak LPH

*Low pH Presoak for Low Pressure Arches Only*

## FEATURES

- Low pH formula

## BENEFITS

- Removes road film, brightens chrome surfaces and leaves windows clear and bright

## RECOMMENDED USES

Full-service automatic vehicle wash systems.

## SPECIFICATIONS

**Color** : Green

**Scent** : None added

**Character** : Non-viscous liquid

**Foam** : Moderate

**pH use dilution** : 2.0 - 3.0

**Phosphorus content** : 7.10%

**Approvals** : cRc

## IMPORTANT

Read and understand the label and Material Safety Data Sheet (MSDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The MSDS is provided with each container shipped. It is also available on our website or from the distributor.

## PRODUCT DIRECTIONS

### EQUIPMENT TO USE

Low pressure spray arch.

### DIRECTIONS TO USE

USE DILUTION: Dilute concentrated product at a ratio of 64 - 104 parts water to one part product. Dilute 5 to 15 parts water to one part product for on-line (C.T.A. only) wheel brightener applications. Apply this low pH presoak through the low pressure spray arch at 40 to 90 PSI. Allow 15 to 20 seconds dwell time before high pressure rinse. DO NOT use this product in any high pressure spray applications. Product should be dispensed through stainless steel and/or plastic equipment. DO NOT put any metal objects (hose clamps, metal weights for keeping foot valves at bottom of container, etc.) into the LPH product container.

## PACKAGING

This product is available in 55 gallon drums (063418).

**PROLine**<sup>TM</sup>

The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information.