

# Speed Fast

## High Performance Cleaner-Degreaser

### FEATURES

- Institutional strength
- Solvent based
- Non-corrosive
- Non-flammable

### BENEFITS

- Low use cost
- Cuts through oils and greases
- Safe on soft metals
- Safer to use

### RECOMMENDED USES

For general cleaning of floors, walls and equipment.

### SPECIFICATIONS

**Color** : Blue

**Scent** : Solvent odor

**Character** : Clear, non-viscous liquid

**Foam** : High

**pH use dilution** : 9.0 - 11.5

**Phosphorus content** : Not over 0.65%

**Approvals** : cRc

### IMPORTANT

Read and understand the label and Material Safety Data Sheet (MSDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The MSDS is provided with each container shipped. It is also available on our website or from the distributor.

### PRODUCT DIRECTIONS

#### EQUIPMENT TO USE

Spray bottle, mop and pail, sponge, cleaning cloth, appropriate measuring device.

#### DIRECTIONS TO USE

USE DILUTION: 2-3 ounces per gallon of water. **Light Duty Cleaning:** When cleaning surfaces such as floors, walls, countertops, cabinets, appliances, chrome fixtures, tile, etc., dilute 2-3 ounces of this product to 1 gallon of warm water (110°-120°F). **Medium Duty Cleaning:** When cleaning surfaces such as the exterior of stoves and ovens, grills, hoods, air filtering systems, carpet, etc., dilute 3-6 ounces of this product to 1 gallon of warm water (110°-120°F). This product may also be used as a laundry prespotter at this dilution. Always pretest product on fabric to assure it will not damage or discolor cloth. Wet fabric prior to application of product. **Heavy Duty Cleaning:** When cleaning surfaces such as industrial equipment, machinery, engines, automotive parts, white wall tires, concrete, etc., dilute 6-12 ounces of this product to 1 gallon of warm water (110°-120°F). NOTE: When mechanically dispensing this product, do not use at water temperatures that exceed 160°F.

### PACKAGING

This product is available in 55 gallon drums (063423).

PROLINE<sup>TM</sup>

The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information.