

FEATURES

- Institutional strength
- Non-foaming
- Contains no hydrochloric acid
- Phosphate free

BENEFITS

- Fast, efficient lime removal
- Designed for deliming dishmachines
- Safe on ice machines
- Environmentally friendly

RECOMMENDED USES

For removing lime from institutional equipment surfaces, including ice machines.

SPECIFICATIONS

Color : Blue
Scent/Odor : None added
Character : Clear, non-viscous liquid
Foam : Low

pH use dilution : 1.5-3.0
Phosphorus content : 0.0%
Approvals : cRc

**IMPORTANT**

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS**EQUIPMENT TO USE**

Abrasive pad or stiff brush.

DIRECTIONS TO USE

Note: Do not use on aluminum. USE DILUTION: For general use, use 1-2 ounces to 3 gallons of water. Initial treatment: Use 2-3 ounces per gallon of water. Allow areas of heavy deposits to soak for several minutes, then brush surface. For ice machines, use 1 ounce to 2 gallons of water.

DISHMACHINE:

1. Drain, flush, and clean out machine. Never add lime solvent to dishmachine containing warewashing detergent.
2. Close drain valve, fill tank(s) with hot water.
3. Add lime solvent at 4 ounces (1/2 cup) per each gallon of water.
4. Turn on pumps until lime can be brushed or flushed away.
5. Drain tank and flush. Always use rubber gloves if product may contact hands.

ICE MACHINE INTERIOR, PARTS AND BIN: Dilute product at 1 ounce to 2 gallons of water. Spray diluted product on surface. Scrub with brush, if needed. Rinse thoroughly with water. Sanitize with approved sanitizer. Let air dry.

PACKAGING

This product is available in 2/1 gallon cases (077070) and 4/1 gallon cases (077074).

