

<u>LIME OFF</u>

High Strength, Non-Foaming Lime Solvent

FEATURES

- Institutional strength acid
- Non-foaming
- Designed for regular use
- Non-abrasive

RECOMMENDED USES

For removing lime from institutional equipment surfaces.

SPECIFICATIONS

Color	:	Straw	pH use dilution	:	1.5 - 3.0
Scent/Odor	:	Acidic	Phosphorus content	:	12.1%
Character	:	Clear, non-viscous liquid	Approvals	:	cRc
Foam	:	Non-foamer			

BENEFITS

• Fast, efficient lime removal

Extends life of equipmentWon't harm surfaces

Designed for deliming dishmachines

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Abrasive pad or stiff brush, rubber gloves and chemical goggles

DIRECTIONS TO USE

USE DILUTION: Use this product at 1-2 oz. per 3 gallons water for general lime control.

INITIAL TREATMENT:

Use 2-3 ounces per gallon of water. Allow areas of heavy lime deposit to soak for several minutes, then brush surface. DISHMACHINE:

1. Drain, flush, and clean out machine. Never add lime solvent to dish-machine containing warewashing detergent.

2. Close drain valve, fill tank(s) with hot water.

3. Add lime solvent at 4 ounces (1/2 cup) per each gallon of water.

4. Turn on pumps until lime can be brushed or flushed away.

5. Drain tank and flush. Always use rubber gloves if product may contact hands.

Note: Do not use on aluminum.

PACKAGING

This product is available in 4/1 gallon cases (5972175) and 15 gallon drums (5530140).

