

### Heavy-Duty Lime solvent for General and Recirculation Lime Removal

#### FEATURES

- Institutional strength acid
- Non-foaming
- Designed for regular use
- Non-abrasive
- Phosphate free

#### RECOMMENDED USES

For removing lime from institutional equipment surfaces.

#### SPECIFICATIONS

**Color** : Green  
**Scent/Odor** : None added  
**Character** : Clear, non-viscous liquid  
**Foam** : Low

#### BENEFITS

- Fast, efficient lime removal
- Designed for deliming dishmachines
- Extends life of equipment
- Won't harm surfaces
- Environmentally friendly



**pH use dilution** : 1.5 - 3.0  
**Phosphorus content** : 0.0%  
**Approvals** : cRc

#### IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

#### PRODUCT DIRECTIONS

##### EQUIPMENT TO USE

Abrasive pad or stiff brush.

##### DIRECTIONS TO USE

**NOTE:** DO NOT USE ON ALUMINUM. Use at 1-2 ounces of product per 2 gallons of water for general lime control.

**INITIAL TREATMENT:** Use 2-3 ounces per gallon of water. Allow areas of heavy lime deposit to soak for several minutes, then brush surface.

##### DISHMACHINE:

1. Drain, flush, and clean out machine. Never add lime solvent to dishmachine containing warewashing detergent.
2. Close drain valve, fill tank(s) with hot water.
3. Add lime solvent at 4 oz. (1/2 cup) for each gallon of water.
4. Turn on pumps until lime can be brushed or flushed away.
5. Drain tank and flush. Always use rubber gloves if product may contact hands.

**DO NOT LET DELIMER SOLUTION REMAIN IN UNATTENDED DISH MACHINE.**

#### PACKAGING

This product is available in 4/1 gallon cases (063837).