

A Quality Lime Solvent for General and Recirculation Lime Removal

### FEATURES

- Concentrated acid formula
- Non-foaming
- Designed for regular use
- Non-abrasive

### BENEFITS

- Removes lime fast and efficiently
- Excellent for deliming dishmachines
- Extends life of equipment
- Won't harm surfaces

### RECOMMENDED USES

To remove lime from institutional equipment surfaces.

### SPECIFICATIONS

**Color** : Orange

**Scent/Odor** : None added

**Character** : Clear, non-viscous liquid

**Foam** : Low

**pH use dilution** : 1.5 - 3.0

**Phosphorus content** : 0.0%

**Approvals** : cRc



### IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

### PRODUCT DIRECTIONS

#### EQUIPMENT TO USE

Abrasive pad and stiff brush.

#### DIRECTIONS TO USE

Do not use on aluminum. Use this product at 1-2 oz. per 1 gallon of water for general lime control.

**USE DILUTION:** For dishmachines, use 5-6 ounces to each gallon of water. For general use, use 1-2 oz. per 1 gallon of water. **INITIAL TREATMENT:** Use 3-4 ounces per gallon of water. Allow areas of heavy lime deposit to soak for several minutes, then brush surface.

#### DISHMACHINE:

1. Drain, flush, and clean out machine. Never add lime solvent to dishmachine containing warewashing detergent.
2. Close drain valve, fill tank(s) with hot water.
3. Add lime solvent at 5-6 ounces per each gallon of water.
4. Turn on pumps until lime can be brushed or flushed away.
5. Drain tank and flush.

**DO NOT LET DELIMER SOLUTION REMAIN IN UNATTENDED DISH MACHINE.**

### PACKAGING

This product is available in 4/1 gallon cases (060950).