

Lime Solvent

Heavy Duty Lime Solvent for General and Recirculation Lime Removal

FEATURES

- Institutional strength acid
- Non-foaming
- Designed for regular use
- Non-abrasive
- Phosphate free

BENEFITS

- Fast, efficient lime removal
- Designed for deliming dishmachines
- Extends life of equipment
- Won't harm surfaces
- Environmentally friendly



RECOMMENDED USES

For removing lime from institutional equipment surfaces.

SPECIFICATIONS

Color	: Green	pH use dilution	: 1.5 - 3.0
Scent/Odor	: None added	Phosphorus content	: 0.0%
Character	: Clear, non-viscous liquid	Approvals	: cRc
Foam	: Low		

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Abrasive pad or stiff brush.

DIRECTIONS TO USE

Note: Do not use on aluminum.

USE DILUTION: For general use, use 1-2 ounces to 2 gallons of water.

INITIAL TREATMENT: Use 2-3 ounces per gallon of water. Allow areas of heavy deposits to soak for several minutes, then brush surface.

DISHMACHINE:

1. Drain, flush, and clean out machine. Never add lime solvent to dishmachine containing warewashing detergent.
2. Close drain valve, fill tank(s) with hot water.
3. Add lime solvent at 4 ounces (1/2 cup) for each gallon of water.
4. Turn on pumps until lime can be brushed or flushed away.
5. Drain tank and flush. Always use rubber gloves if product may contact hands.

DO NOT LET DELIMER SOLUTION REMAIN IN UNATTENDED DISH MACHINE.

PACKAGING

This product is available in 4/1 gallon cases (063590).

PROline