

# LIQUID FURY

Non-Chlorinated Liquid Warewash Detergent

### **FEATURES**

- Contains metal protectors
- Non-chlorinated / metal-safe
- Contains water conditioners

### **BENEFITS**

- Prolongs dishmachine life
- Safe on aluminum
- Can be used in most water hardness conditions



#### **RECOMMENDED USES**

For institutional warewashing, pot washers and hood recirculation cleaning systems.

#### **SPECIFICATIONS**

Color :	Orange
Scent/Odor :	None added
Character :	Clear, non-viscous liquid
Foam :	Non-foamer

pH use dilution	:	10.8 - 11.5
<b>Phosphorus content</b>	:	0.0%
Approvals	:	cRc, NSF A1

### **IMPORTANT**

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

# **PRODUCT DIRECTIONS**

#### EQUIPMENT TO USE

Recommended automatic warewash dispensing equiment.

#### **DIRECTIONS TO USE**

**USE DILUTION:** Concentration varies due to environmental conditions. Your sanitation specialist will properly adjust product concentrations to meet your needs.

**FOR LOW TEMPERATURE WAREWASHING:** 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. 4. In rinse cycle, use a recommended rinse additive. 5. Sanitize using an approved chlorinated sanitizer at 50 ppm. Test using chlorine test papers or a liquid chlorine test kit. 6. Allow dishes to air dry.

**FOR HIGH TEMPERATURE WAREWASHING:** 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. Maintain wash temperature at 150°-160°F. 4. In rinse cycle, use a recommended rinse additive. Maintain rinse temperature at 180°-190°F. 5. Allow dishes to air dry.

**FOR AUTOMATIC HOOD CLEANING:** Formulated to quickly emulsify greasy oils without harm to equipment surfaces. Product should be fed directly from shipping container for convenient use.

# PACKAGING

This product is available in 4/1 gallon cases (057257), 5 gallon pails (057259) and 15 gallon drums (057261).

