



FEATURES

- Concentrated
- Excellent water conditioning
- Contains metal protectors

BENEFITS

- Efficient and economical
- Can be used in all water hardness conditions
- Safe on aluminum and dishware with precious metals

RECOMMENDED USES

For use on aluminum and dishware with precious metals such as gold and silver at a concentration between 500-1500 ppm. At a concentration of 2500 ppm, there is still a risk of damage if the protective glaze has been removed. For institutional mechanical warewash use ONLY.

SPECIFICATIONS

Color	: Colorless	pH use dilution	: > 13.0
Scent	: None	Phosphorus content	: 0.46%
Character	: Clear to slightly hazy, non-viscous liquid	Approvals	: cRc
Foam	: Non-foamer		



IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Recommended automatic warewash dispensing equipment.

DIRECTIONS TO USE

USE DILUTION: Concentration varies due to environmental conditions. Your sanitation specialist will adjust properly to meet your needs. **FOR LOW TEMPERATURE WAREWASHING:** 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. 4. In rinse cycle, use a recommended rinse additive. 5. Sanitize using an approved chlorinated sanitizer at 50 ppm. Test using chlorine test papers or a liquid chlorine test kit. 6. Allow dishes to air dry. **FOR HIGH TEMPERATURE WAREWASHING:** 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. Maintain wash temperature at 150 -160 °F. 4. In rinse cycle, use a recommended rinse additive. Maintain rinse temperature at 180 -190 °F. 5. Allow dishes to air dry. **FOR AUTOMATIC HOOD CLEANING:** Formulated to quickly emulsify greasy oils without harm to equipment surfaces. Product should be fed directly from shipping container for convenient use.

PACKAGING

This product is available in 5 gallon pail (5950523).

