

## Non-Chlorinated Liquid Warewash Detergent

### FEATURES

- Contains metal protectors
- Non-chlorinated
- Water conditioners

### BENEFITS

- Prolongs dishmachine life
- Designed for all temperature warewash applications
- Can be used in most water hardness conditions



### RECOMMENDED USES

For institutional high and low temperature mechanical warewashing and hood recirculation cleaning systems.

### SPECIFICATIONS

**Color** : Orange  
**Scent/Odor**: None added  
**Character** : Clear, non-viscous liquid  
**Foam** : None

**pH use dilution** : 10.8 - 11.5  
**Phosphorus content** : 0.0%  
**Approvals** : cRc

### IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

### PRODUCT DIRECTIONS

#### EQUIPMENT TO USE

Recommended dispensing system.

#### DIRECTIONS TO USE

**USE DILUTION:** Concentration varies due to environmental conditions. Your sanitation specialist will properly adjust product concentrations to meet your needs.

**FOR LOW TEMPERATURE WAREWASHING:** 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. 4. In rinse cycle, use a recommended rinse additive. 5. Sanitize using an approved chlorinated sanitizer at 50 ppm. Test using chlorine test papers or a liquid chlorine test kit. 6. Allow dishes to air dry.

**FOR HIGH TEMPERATURE WAREWASHING:** 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. Maintain wash temperature at 150°-160°F. 4. In rinse cycle, use a recommended rinse additive. Maintain rinse temperature at 180°-190°F. 5. Allow dishes to air dry.

**FOR AUTOMATIC HOOD CLEANING:** Formulated to quickly emulsify greasy oils without harm to equipment surfaces. Product should be fed directly from shipping container for convenient use.

### PACKAGING

This product is available in 5 gallon pails (060881).