

miniMAX

MECHANICAL WAREWASH DETERGENT

FEATURES

- High alkaline
- Concentrated
- Excellent water conditioning
- Totally Enclosed Dispensing (TED™)

BENEFITS

- Removes tough, burned-on soil
- Efficient and economical
- Can be used in all water hardness conditions
- Eliminates spill hazard

RECOMMENDED USES

For Institutional Use Only. DO NOT USE ON ALUMINUM OR ANY SOFT OR PRECIOUS METALS.

SPECIFICATIONS

Color : Red
Scent/Odor: None added/Amine
Character : Clear, non-viscous liquid
Foam : Non-foamer

pH use dilution : 11.0-12.5
Phosphorus content : 0.7%
Approvals : cRc



IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

MiniMax docking station, Freedom DE or comparable warewash detergent dispenser.

DIRECTIONS TO USE

USE DILUTION: Concentration varies due to environmental conditions. Your sanitation specialist will adjust properly to meet your needs.

FOR LOW TEMPERATURE WAREWASHING: 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. 4. In rinse cycle, use a recommended rinse additive. 5. Sanitize using an approved chlorinated sanitizer at 50 ppm. Test using chlorine test papers or a liquid chlorine test kit. 6. Allow dishes to air dry. **FOR HIGH TEMPERATURE WAREWASHING:** 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. Concentration will vary due to environmental conditions. Maintain wash temperature at 150°-160°F. 4. In rinse cycle, use a recommended rinse additive. Be sure rinse injector is working properly. Maintain rinse temperature at 180°-190°F. 5. Allow dishes to air dry.

KEEP FROM FREEZING. Do not use on aluminum.

PACKAGING

This product is available in 2/3100 mL cases (4486191).