

# **ELIMINATE**<sup>™</sup>

BENEFITS

Counteracts malodors

Can be diluted effectively

lipstick, ink, grease, oil

**Phosphorus content :** 0.0%

Effective on tar, adhesives, crayon,

: N/A

: cRc

**Deodorizing Grease-Cutter** 



## **FEATURES**

- Great citrus fragrance
- Water emulsifiable
- 100% active natural solvents

# **RECOMMENDED USES**

Degreasing and odor elimination for cleaning and industrial applications.

#### **SPECIFICATIONS**

Color :	Yellow
Scent/Odor:	Citrus
Character :	Clear, non-viscous liquid

## **IMPORTANT**

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

pH use dilution

**Approvals** 

## **PRODUCT DIRECTIONS**

#### **EQUIPMENT TO USE**

Appropriate sprayer or application device.

#### **DIRECTIONS TO USE**

DEGREASING DIRECTIONS: For General Degreasing: Use 1 oz. per 1.5 gallons of water. For Incidental, hard to remove soils, such as gum and ink: Apply full strength, but sparingly. Allow this product to penetrate soil. Agitate if necessary. Rinse surfaces thoroughly. CAUTION: like any solvent, this product can affect surfaces such as plastic and rubber. Test surfaces in an obscure area to determine safety and contact time required. FOR DRAIN LINES & GREASE TRAPS: Add 4-6 oz. directly into drains at the end of each day. Flush with hot water in the morning. FOR DUMPSTERS, GARBAGE CANS, MACHINERY, ETC. Add 1 oz. per 1.5 gallons of warm water. Spray or mop on surfaces. Allow to stand 2-5 minutes. Brush if necessary. Rinse. DEODORIZING DIRECTIONS: FOR CARPETS & UPHOLSTERY: Add 0.5 oz. of this product for each 4 gallons of solution. Add directly to solution tanks (overuse in extraction equipment may cause swelling of rubber 0 rings). FOR RESTROOMS, FLOORS, ETC.: Add 1 oz. to 3 gallons of cleaning solution. FOR AIR FRESHENING: Add 1 oz. per 1.5 gallons of water. Solution may be fogged or sprayed as desired. CAUTION: Do not fog in a confined area when people are present. Respiratory irritation may result. FOR SEWAGE TREATMENT: Treat the sewage as it enters the plant collection system at the rate of three to five parts of this product for each million parts of sewage. Introduction into the sewage system is best accomplished by the "slo-drip" method. FOR CAR WASH RECLAIM PITS: For every 1,000 gallons of reclaim add 1 gallon of this product directly to the pit. FOR ANIMAL CARE FACILITIES, PIG & CHICKEN FARMS: Recommended for refuse containers, waste areas, floors, etc., use 1 oz. per 1.5 gallons of water & mop, spray or brush on. Rinse thoroughly.

# PACKAGING

**C** 

This product is available in 6/1 quart cases (6110850) and 4/1 gallon cases (5012941).



S

07/21

Ε

S

L003610

Α

Ε

R

S

LE

Copyright© 2021 U S Chemical, Watertown WI 53094 www.uschemical.com

Π

Ε

G

R

Ε

&

