




CONCOURSE™

Permanent Sealer For Concrete and Other Non-Resilient Flooring



FEATURES

- Permanent polyurethane sealer
- Superior adhesion
- High gloss finish

RECOMMENDED USES

Permanent sealer for non-resilient floor surfaces such as concrete, terrazzo, quarry, slate, brick, exposed aggregates.

SPECIFICATIONS

Color : White

Scent/Odor: Bland

Character : Opaque, non-viscous liquid

Foam : Non-foamer

BENEFITS

- Excellent for non-resilient floors
- Will not dust or flake off
- Provides superior appearance



pH use dilution : 8.2-9.2

Phosphorus content : 0.2%

Approvals : cRc

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Clean mop, finish applicator or tank sprayer.

DIRECTIONS TO USE

NOTE: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials. PREPARATION: Thoroughly clean the floor surface. Be sure to remove all grease, oil, and other soils. Rinse completely with clean water and allow to dry. APPLICATION: Apply using a mop, applicator, or tank sprayer. Spray application is recommended for rough or vertical surfaces. Allow 30 minutes to one hour drying time, depending on conditions, between coats. For best results the first coat should be applied thin, followed by a heavier second coat. Allow 8-12 hours before subjecting to heavy traffic. Do not apply to concrete less than 30 days old, or to surfaces where conditions of standing water are likely to exist. MAINTENANCE: Concourse™ may be maintained by damp mopping or machine scrubbing. For enhanced gloss and appearance, Concourse™ may be coated with any Misco floor finish. COVERAGE: Will depend on the condition of the surface to be treated. On rough or porous surfaces 500-1000 sq. ft./gal. On smoother and less porous surfaces 1000-1500 sq.ft./gal. NOTE: Concourse™ is designed to be a permanent type seal. Do not apply to resilient floor surfaces where ease of removability is desired.

PACKAGING

This product is available in 5 gallon pails (065448).

L003661

Copyright© 2021 U S Chemical, Watertown WI 53094
www.uschemical.com

07/21