

Di-Solv

Non-Foaming Lime Solvent

Di-Solv is an acid detergent formulated to quickly remove lime and other mineral deposits from metal surfaces. Its non-foaming character allows its use in recirculation systems such as dishmachines. Special additives make it rinse free and clear from all metal surfaces.

Specifications

Color	Straw
Scent/Odor	None added
Character	Clear, non-viscous liquid
Foam	Low
pH Use Dilution	1.5 - 3.0
Phosphorus Content	0.0%
Approvals	cRc

Pack Sizes

057027 4/1 gallon case



Directions For Use

Equipment: Abrasive pad or stiff brush.

NOTE: Do not use on aluminum.

Use Dilution: For general use, use 1-2 ounces to 3 gallons of water. For ice machines, use 1 ounce to 2 gallons of water.

Initial Treatment:

1. Use 2-3 ounces per gallon of water.
2. Allow areas of heavy deposits to soak for several minutes.
3. Brush surface.

Dishmachine:

1. Drain, flush and clean out machine. Never add lime solvent to dishmachine containing warewashing detergent.
2. Close drain valve, fill tank(s) with hot water.
3. Add lime solvent at 4 ounces (1/2 cup) per gallon of water.

4. Turn on pumps until lime can be brushed or flushed away.
5. Drain tank and flush. Always use rubber gloves when handling this product.

Do not let delimer solution remain in unattended dishmachine.

Ice Machine Interior, Parts and Bin:

1. Dilute product at 1 ounce to 2 gallons of water.
2. Spray diluted product on surface.
3. Scrub with brush, if needed.
4. Rinse thoroughly with water.
5. Sanitize with approved sanitizer.
6. Let air dry.

Product Demo



Scan the QR code with your mobile device to view an instructional video featuring this product!

Safety Reminder

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

