

Drop-Off

Dish Machine Rinse Additive

Drop-Off is a very effective rinse additive for high temperature mechanical dishwashing final rinse applications. It lowers water surface tension to speed surface drainage and provides clean, spot free dishware. This product will do an effective job in most water conditions and can be dispensed through any commonly used rinse additive dispensing equipment.

Specifications

Color	Blue
Scent/Odor	None
Character	Clear, slightly viscous liquid
Foam	Low to none
pH Use Dilution	5.0 - 8.0
Phosphorus Content	0.0%
Approvals	cRc

Pack Sizes

057021	4/1 gallon case
057023	5 gallon pail



Directions For Use

Equipment: Recommended warewash rinse injector.

Use Dilution: Concentration varies due to environmental conditions.

FOR HIGH TEMPERATURE WAREWASHING:

1. Pre-flush and/or scrape dishes before washing.
2. Rack dishes properly. Place dishes in machine.
3. Wash using a recommended mechanical warewash detergent. Should maintain 150°-160°F wash temperature.
4. For rinse cycle, use this product. Should maintain 180°-190°F rinse temperature.
5. Allow dishes to air dry.

Product Demo



Scan the QR code with your mobile device to view an instructional video featuring this product!

Safety Reminder

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

