Liquid Fury Metal Safe Detergent

Providing Exceptional Quality Since 1962

U S Chemical



Liquid Fury is a non-chlorinated metal safe liquid warewash detergent designed for all temperature warewashing and for use in automatic hood cleaning systems. It is fortified with special water conditioners and grease emulsifiers to tackle the tough jobs. It is very economical, yet strong enough for most applications.

Specifications

Color	Orange
Scent/Odor	None added
Character	Clear, non-viscous liquid
Foam	Non-foamer
pH Use Dilution	10.8 - 11.5
Phosphorus Content	0.0%
Approvals	cRc, NSF A1

Pack Sizes

057257	4/1 gallon case
057259	5 gallon pail



Directions For Use

Equipment: Recommended automatic warewash dispensing equipment.

Use Dilution: Concentration varies due to environmental conditions. Your sanitation specialist will properly adjust product concentrations to meet your needs.

For Low Temperature Warewashing:

- 1. Pre-flush and/or scrape dishes before washing.
- 2. Rack dishes properly. Place dishes in machine.
- 3. Wash using this product.
- 4. In rinse cycle, use a recommended rinse additive.
- 5. Sanitize using an approved chlorinated sanitizer at 50 ppm.
- Test using chlorine test papers or a liquid chlorine test kit. 6. Allow dishes to air dry.

Product Demo



Scan the QR code with your mobile device to view an instructional video featuring this product!

Safety Reminder

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

For High Temperature Warewashing:

temperature at 180°-190°F.

shipping container for convenient use.

5. Allow dishes to air dry.

1. Pre-flush and/or scrape dishes before washing.

2. Rack dishes properly. Place dishes in machine.

3. Wash using this product. Maintain wash temperature at 150°-160°F.

For Automatic Hood Cleaning: Formulated to quickly emulsify greasy oils

without harm to equipment surfaces. Product should be fed directly from

4. In rinse cycle, use a recommended rinse additive. Maintain rinse

