Providing Exceptional Quality Since 1962

🛈 U S Chemical

All Temperature Warewashing Detergent

Temp Det is a non-chlorinated, liquid warewash detergent designed for all temperature warewashing. It is fortified with special water conditioners and grease emulsifiers to tackle the tough jobs. It is very economical, yet strong enough for most applications.

Color	Red/orange
Scent/Odor	None
Character	Clear, non-viscous liquid
Foam	Non-foamer
pH Use Dilution	10.0 - 12.0
Phosphorus Content	0.0%
Approvals	cRc

Pack Sizes	
057560	4/1 gallon case
057562	5 gallon pail
4391395	15 gallon drum

Directions For Use

Equipment: Recommended dispensing system.

Use Dilution: Concentration varies due to environmental conditions. Your sanitation specialist will properly adjust product concentration to meet your needs.

For Low Temperature Warewashing:

- 1. Pre-flush and/or scrape dishes before washing.
- 2. Rack dishes properly. Place dishes in machine.
- 3. Wash using this product.
- 4. In rinse cycle, use a recommended rinse additive.
- 5. Sanitize using an approved chlorinated sanitizer at 50 ppm*.
- Test using chlorine test papers or a liquid chlorine test kit. 6. Allow dishes to air dry.

Product Demo



Scan the QR code with your mobile device to view an instructional video featuring this product!

Safety Reminder

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.



For High Temperature Warewashing:

- 1. Pre-flush and/or scrape dishes before washing.
- 2. Rack dishes properly. Place dishes in machine.
- 3. Wash using this product. Maintain wash temperature at 150°-160°F.
- 4. In rinse cycle, use a recommended rinse additive. Maintain rinse temperature at 180°-190°F.
- 5. Allow dishes to air dry.
- *ppm = parts per million
- NOTE: Do not use on aluminum.



Copyright ©2021

U S Chemical • Watertown, Wisconsin 53094

www.uschemical.com