SOUR/SOFT

nicro

FEATURES

BENEFITS

•

•

Convenient - safe - simple

Extremely low use rates

Improves results

- Combination sour and softening agent
- Hyper-concentrated formula
- Iron inhibiting formula

RECOMMENDED USES

For institutional laundry use ONLY. DO NOT USE IN HOMESTYLE MACHINES.

SPECIFICATIONS

Color :	Purple	pH use dilution	:	5.5-6.5
Scent/Odor :	Citrus	Phosphorus content		9.5%
Character :	Opaque, slightly viscous liquid	Approvals	:	N/A
Foam :	None	Water Temperature		All

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

PRODUCT DIRECTIONS

DIRECTIONS TO USE

USE DILUTION: Concentration varies due to environmental conditions and load size. Your sanitation specialist will adjust properly to meet your needs.

1. Pre-sort laundry prior to wash.

2. Pre-soak and/or pre-spot laundry when necessary.

3. Place proper amount of soiled fabric into laundry machine.

*Specially formulated for optimal results when used with OMNI's LUX Advanced Oxidation System.

4. In wash cycle, inject microTECH[™] Break and microTECH[™] Suds.
5. When bleaching, inject microTECH[™] Destainer or microTECH[™] Oxygen Bleach.

6. When souring and softening, inject microTECH[™] Sour/Soft. A final pH of 5.5-6.5 is recommended for the fabric.

*This product is compatible with ozone laundry systems.

*This product can be used in all water temperatures. Your Chemical Specialist will adjust product concentrations based on results.

PACKAGING

This product is available in a 1/1.5 gallon case (101105577) and a 2/1.5 gallon case (5337083).

OMNI's patented system allows the user to use less hot water, less total water and improves disinfection during the wash process.



L004207 Copyright© 2021 07/21 U S Chemical, Watertown WI 53094

microtec SAUR/SA