

## ICE-STRIP

### FEATURES

- Contains no ammonia
- Concentrated formula
- Works quickly and completely

### RECOMMENDED USES

For removal of floor finishes and sealers.

### SPECIFICATIONS

**Color** : Colorless

**Scent** : Solvent

**Character** : Clear, non-viscous liquid

### BENEFITS

- Non-irritating to residents
- Economical in use
- Labor saving

**pH use dilution** : > 13.0

**Phosphorus content** : 0.0%

**Approvals** : cRc



### IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

### PRODUCT DIRECTIONS

#### EQUIPMENT TO USE

Clean mop and bucket, scrubbing machine with stripping pads, wet vacuum, personal protective equipment.

#### DIRECTIONS TO USE

Blockade areas to be stripped. Floors will become very slippery when stripper is applied. Exercise caution. 1. Use appropriate personal protective equipment. Dilute solution 1:4-1:6 with cool water for removing a heavy build-up of floor finish (ultra high speed). Dilute solution 1:8-1:10 with cool water for removing a light build-up of floor finish (conventional). 2. Apply liberal amounts of solution uniformly to floor with a mop. If splashing occurs, wipe off surfaces with a clean rag dampened with water. 3. Let stripper solution soak for 5-10 minutes. Mop agitate to loosen finish. Rewet as necessary, do not allow solution to dry on floor. Longer soak times may be necessary in cases of extreme buildup. NOTE: When removing chemically "resistant" sealers, reapply an additional amount of stripper solution after an initial five minute soak time, wait an additional five minutes and then scrub. Repeat as needed. 4. Hand or machine scrub thoroughly using stripping pads or stripping brush. 5. Pick-up all of the solution with a clean mop, wet vac or automatic scrubber. 6. Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry. Thoroughly rinse floor with clean water using a mop and bucket. 7. Let floor dry completely before applying recommended floor sealer or finish.

### PACKAGING

This product is available in a 4/1 gallon case (100977839) and 5 gallon pail (5548041).