

## GX-2001

### High Gloss Sealer and Finish

#### FEATURES

- Seal and finish in one product
- Maintain with 175-1500 RPM
- Excellent Gloss

#### BENEFITS

- Simplifies hardwood maintenance
- Easy to use and maintain
- Brilliant results

#### RECOMMENDED USES

Sealing and finishing terrazo, quarry tile, brick, slate, marble, granite and unglazed ceramic and Mexican tile. Can also be used on resilient floors.

#### SPECIFICATIONS

**Color** : White  
**Scent/Odor** : None Added  
**Character** : Milky, non-viscous liquid

**pH use dilution** : 8.8 - 9.3  
**Phosphorus content** : 0.08%  
**Solids** : 20%



#### IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

#### PRODUCT DIRECTIONS

##### EQUIPMENT TO USE

Appropriate stripping supplies and equipment, dust mop, clean mop, mop bucket, bunishing equipment, deep scrubbing equipment, wet floor signs.

##### DIRECTIONS TO USE:

1. Strip floor according to stripper label directions.
2. Apply 2 to 3 coats of GX-2001 using a clean mop. If higher gloss is desired apply additional coats.
3. Allow 40-50 minutes drying time between coats.

##### MAINTENANCE:

1. Dust mop or sweep.
2. Clean floor with a recommended cleaner according to label directions.
3. If desired, spraybuff or high speed buff using GENESIS GX-1000 or GX-1500 in order to maintain desired gloss.

##### RECOATING:

1. Dust mop or sweep.
2. Deep scrub floor using a neutral cleaner according to label directions.
3. Apply 1-2 coats using a clean mop

##### REMOVAL:

1. Remove using a recommended stripper according to label directions.

#### PACKAGING

This product is available in 5 gallon bag-in-box (076905).