

TECHNICAL DATA

GX-1000

Ultra High Speed Gloss Restorer

FEATURES

- Polymer-based product
- Dilutable 1:4 with water
- Specially formulated

BENEFITS

Fills in scratches and scuffs

pH use dilution

: 8.5

- Cost effective
- Maintains a continuous "wet look"

RECOMMENDED USES

Mop-on UHS finish restoration.

SPECIFICATIONS

Color : Blue Scent/Odor: Lemon/Ammonia

Phosphorus content: 0.2% **Character**: Cloudy, non-viscous liquid Solids

: 15.0%

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is provided with each container shipped. It is also available on our website or from the distributor.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Clean mop, mop bucket, burninshing equipment, dust mop, wet floor signs.

DIRECTIONS TO USE

For use on all floors maintained with ultra high speed buffing equipment. Coverage is 8,000-10,000 sg. ft. per gallon. To maintain and enhance floor appearance, use GX-1000 at least once per week.

- 1. Prepare floor by dust mopping and top scrubbing with a neutral cleaner and a blue or green pad.
- 2. Dilute 1 part GX-1000 with 4 parts cool water (1:4) and mop apply in an even coat.
- 3. Allow GX-1000 to dry thoroughly. Burnish floor after drying to maximize appearance. Frequency of burnishing and use of GX-1000 will depend on floor traffic conditions. Use the chart below as a guide to determining frequencies.
- 4. Do not pour unused product back into container. NOTE: GX-1000 can also be used on all GENESIS, or other suitable floor finishes to make them compatible with ultra high speed burnishing equipment and procedures. Apply one coat GX-1000 before burnishing the first time.

PACKAGING

This product is available in 4/1 gallon cases (076913).