

GX-2002+ ProX

High-Performance Finish for Infrequent Maintenance



NO INTENTIONALLY ADDED PFAS

FEATURES

- High performance & high durability
- Industry proven formula
- Excellent traffic and mark resistance

BENEFITS

- Great finish value
- Saves time and money
- Protects and enhances floor appearance

RECOMMENDED USES

Low maintenance, high durability floor finishing. For use on all resilient floors.



SPECIFICATIONS

Color : White
Scent : Ammonia
Character : Opaque, non-viscous liquid

pH use dilution : 8.5 - 9.5
Phosphorus content : 0.19%
Solids : 16.5%

IMPORTANT

Read and understand the label and Safety Data Sheet (SDS). These provide a description of hazards, precautions, personal protective equipment, first aid, 24 Hour Emergency lines, storage data and other safe handling information. The SDS is available on our website at www.uschemical.com and is also available by scanning the QR code on the label.

PRODUCT DIRECTIONS

EQUIPMENT TO USE

Mop or floor machine, wet vacuum or bucket with wringer, rubber gloves, eye protection and wet floor signs.

DIRECTIONS TO USE

PREPARATION:

Blockade areas to be stripped or finished. Floors will be very slippery until dry. Before the first application of floor finish, remove all old finish with the recommended stripper.

COATING:

Apply 3 or more medium coats of floor finish with a clean finish mop. Let dry to the touch between coats — about 30 minutes. On porous resilient or stone floors, seal first with 2 coats of recommended sealer.

MAINTENANCE:

For daily cleaning dust mop or sweep. Then wet clean with the recommended cleaner in an autoscrubber or with a damp mop.

BURNISHING:

To renew gloss spray buff as needed with the recommended spray buff, a red or beige pad, and a 175-1500 rpm machine. Or burnish with a UHS pad and a battery, cord electric, or propane machine at 1500-2000+ rpm.

RECOATING:

Dust mop or sweep floor. Scrub floor with an autoscrubber or floor machine using a blue pad and the recommended cleaner at therecommended dilution. Rinse well and let dry. Apply 1-2 new coats of floor finish.

REMOVAL:

1. Remove using a recommended GENESIS floor stripper according to label directions.

PACKAGING

This product is available in 5 gallon BIB (9299674).